

qbbottom

[[Description](#)] [[Usage](#)] [[Options](#)] [[Notes](#)] [[Examples](#)] [[See also](#)]

Description

qbbottom requests the Supervisor to move a job/jobs below other jobs having the same priority.

Usage

qbbottom [*options*] *jobID*... | 0

where *JobID* is one or more job IDs, and 0 is a wild card token representing all the user's jobs.

Options

Option	Description
--running	Bottom running jobs
--pending	Bottom pending jobs
--blocked	Bottom blocked jobs
--active	Bottom active (pending,running,blocked) jobs
--user <i>string</i>	Bottom jobs for user <i>string</i>
--type <i>string</i> --prototype <i>string</i>	Bottom jobs with <i>string</i> type
--status <i>string</i>	Bottom jobs with <i>string</i> status (ex. pending)
--name <i>string</i>	Bottom jobs with <i>string</i> name
--kind <i>string</i>	Bottom jobs of <i>string</i> kind
--pid <i>int</i>	Bottom jobs with process ID <i>int</i>
--pgrp <i>int</i>	Bottom jobs in <i>int</i> process group
--priority <i>int</i>	Bottom jobs with <i>int</i> priority
--cluster <i>string</i>	Bottom jobs in <i>string</i> cluster
--cpus <i>int</i>	Bottom jobs with a total of <i>int</i> subjobs
--xml	Output in XML format
--help	Command help
--version	Command version

Notes

Examples

Move job 12345 to the bottom of the queue within the priority:

```
% qbbottom 12345
```

Move all of user anthony's jobs:

```
% qbbottom --user anthony 0
```

Move all of user anthony's jobs which are running:

```
% qbbottom --running --user anthony 0
```

See also

[qbmodify](#)

[qbtopy](#)